




GROUND LIGHTS SPECIFICATION SHEET



COLLINGWOOD
LIGHTING

01604 495 151
collingwoodlighting.com

-  @collingwoodLED
-  /collingwoodlighting
-  collingwoodled

GL100

Small domed marker light

FEATURES

Wattage	1W (350mA) 2W (700mA)
IP rating	IP68
IK rating	IK07
Colour flexibility	Fixed colour
Walk Over / Drive Over	Walk over
Input	350mA / 700mA
LED Lifetime	70,000h L70 B10
SDCM	3SDCM

INSTALLATION INFORMATION

Cut Out Size	Ø 33mm
Bathroom zone	0
Construction Material	Stainless steel (316)
Weight	221g
Maximum ambient temperature	35°C

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

Walk over - perfect for foot traffic areas such as paths and steps

Marine-grade Stainless Steel 316

IP68

Long-lifetime of 70,000hrs

Low power consumption of 1W

7-year warranty

PHOTOMETRICS @ 25°C

Partcode	Feature I	Colour	Beam angle	350mA		700mA	
				lm	lm/W	lm	lm/W
GL100DX1X27	1 window	2700K	75°	2	2	3	2
GL100DX1X30	1 window	3000K	75°	2	2	4	2
GL100DX1X40	1 window	4000K	75°	3	3	4	2
GL100DX2127	2 windows, 1 direction	2700K	75°	4	4	6	3
GL100DX2130	2 windows, 1 direction	3000K	75°	4	4	8	4
GL100DX2140	2 windows, 1 direction	4000K	75°	6	6	7	4
GL100DX2227	2 windows, 2 directions	2700K	75°	4	4	6	3
GL100DX2230	2 windows, 2 directions	3000K	75°	4	4	8	4
GL100DX2240	2 windows, 2 directions	4000K	75°	6	6	7	4
GL100DX3X27	3 windows	2700K	75°	6	6	9	5
GL100DX3X30	3 windows	3000K	75°	6	6	12	6
GL100DX3X40	3 windows	4000K	75°	9	9	11	5
GL100DX4X27	4 windows	2700K	75°	8	8	12	6
GL100DX4X30	4 windows	3000K	75°	8	8	14	7
GL100DX4X40	4 windows	4000K	75°	12	12	14	7




WIRING INFORMATION

Cable / Flying Lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of Wiring Required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLR/350 1-5	220-240V	Yes	No	0	1	5
PLD UNI-DRIVE 350MA	N/A	Yes	Yes (1-10V)	2	1	10
PLU/700 3-9	N/A	Yes	No	1	3	9

Beam angle: C0/C180 C90/C270



GROUND LIGHTS SPECIFICATION SHEET


ACCESSORIES


JB2 / JB4 / JB6	IP68 waterproof connectors
TUBE/33	Installation tube
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types




COLLINGWOOD
LIGHTING

01604 495 151
collingwoodlighting.com

 @collingwoodLED

 /collingwoodlighting

 collingwoodled

GL100

The GL100 creates a grazing light effect from a domed, marine-grade stainless steel 316 housing. This product is available in five different window styles and three colour temperatures to suit a wide range of applications. This is ideal for providing low-glare, decorative illumination of pathways, decking and steps.