

WALL LIGHTS SPECIFICATION SHEET



COLLINGWOOD
LIGHTING

01604 495 151
collingwoodlighting.com

- @collingwoodLED
- /collingwoodlighting
- collingwoodled

WL070

Silver straight to mains, high output LED wall light

FEATURES

Wattage	5.1W
IP rating	IP65
Colour flexibility	Fixed colour
Tilttable	No
Dimmable	No
Input	Mains AC
LED Lifetime	70,000h L70 B10
SDCM	3SDCM

INSTALLATION INFORMATION

Bathroom zone	2
Inrush Current	60A 0.037ms
Construction Material	Anodised aluminium Copper
Weight	0.9kg
Maximum ambient temperature	40°C

PHOTOMETRICS @ 25°C

Partcode	Finish	Colour	Beam angle	CRI	lm	lm/W	lx @ 1m
WL070SNBM27	Silver	2700K	12°	>80Ra	510 / 255	100	3147 / 1573
WL070SNBM30	Silver	3000K	12°	>80Ra	550 / 275	108	3394 / 1697
WL070SNBM40	Silver	4000K	12°	>80Ra	560 / 280	110	3455 / 1727
WL070BNBM27	Black	2700K	12°	>80Ra	510 / 255	100	3147 / 1573
WL070BNBM30	Black	3000K	12°	>80Ra	550 / 275	108	3394 / 1697
WL070BNBM40	Black	4000K	12°	>80Ra	560 / 280	110	3455 / 1727
WL070CNBM27	Copper	2700K	12°	>80Ra	510 / 255	100	3147 / 1573
WL070ZNBM27	Bronze	2700K	12°	>80Ra	510 / 255	100	3147 / 1573
WL070ZNBM30	Bronze	3000K	12°	>80Ra	550 / 275	108	3394 / 1697
WL070ZNBM40	Bronze	4000K	12°	>80Ra	560 / 280	110	3455 / 1727

WIRING INFORMATION

Cable / Flying Lead	0.3m
Type of Wiring Required	Parallel

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	N/A	N/A	N/A

ACCESSORIES

N/A	No accessories required
-----	-------------------------

GUARANTEE / WARRANTY

7 year extended warranty available

FEATURES & BENEFITS

Improved look and feel with single LED

Bi-directional, straight to mains wall light, perfect for framing entrances and illuminating columns

Solid copper option gradually ages over time to offer a wonderful antique effect

Long lifetime of 70,000hrs

7 year warranty

Beam angle: 12°

